

Baler ARTechnic PBs700 for hard plastic hydraulic bale ejection system



Advantages of the machine:

- **The moving of the pressing plate is kept extremely rigid and straight.** The hydraulic cylinder does not take the bending forces from the pressing plate, which could lead to its damage. These forces are taken over by special plastic guides which are tailored to the corners of the chamber. The guides are made from specially chosen plastic, which is characterized by very high resistance to abrasion. Therefore, these elements are extremely durable. This avoids the need to control the tilt of the pressing plate. Because of all this you can easily exploit our machines, even for very demanding materials, without worrying of an improperly use of the machine.

- **The steel construction** of our machines is designed to withstand loads far in excess of the rated load for the different models (this is why our machines have a generally bigger own mass compared to the competition)

- **A system to prevent the decompressing of material** after subsequent cycles of work.

- **Possibility to bind the packages (bales) with all commonly used materials** like a polyester tape, twine or

steel wire;

- **The possibility of producing specified machines** concerning the customer's request e.g. changes in the stroke of the pressing plate, changes in the loading hole, changes in the size of the bale, etc.

- **Possibility to choose the version of the controller** and to choose additional options, depending on individual needs


- **Unmanned and durable** hydraulic system

- **No hidden costs of operating the machine**

Technical specification

Number of chambers:	single	Loading:	frontal
Charging hole:	1070 x 620 mm	Bale tying:	manual
Max. pressure:	700kN (70 tons)	Bale launch:	Automatic, (hydraulic ejector)
Unit pressure:	9,09 kg/cm²	Supply:	400/50 [V/Hz]
Bale dimensions:	1100 x 700 x 600-1200	Engine power:	7,5 kW
Bale weight:	ok. 400 kg (plastic ABS)	Work cycle:	ca. 42 sec
Productivity:	ok. 2 bale/h	Weight:	3500 kg

Dimension

	LEGEND		[mm]
	A	height	
B	width		1670
C	depth		1000
D	transport height		2350
E	door height		1750
F	depth with open door		2100
G	filling inlet		1070 x 620


Available steering types

Steering x (EXTRA)

Features

- Controller PLC
- Automatic digital steering of the work cycle
- Finished-bale signal
- LCD display
- Stepless maximum pressure regulation with 1 ton progression
- Stepless bale height regulation with 2 cm progression
- Daily/weekly/monthly statistics – the readout of the number of finished bales with their weight estimation
- Different programs for different materials
- Possibility of regulating the length of time for which the pressing plate stays in the lower position
- **NEW !! The ability to connect the machine to the statArtechnic**

Control Panel



1. Main switch with the possibility to lock in position "0" (prevents from an use of the machine by unauthorized persons)
2. The white light "PACKET" indicates that the press has achieved the maximum filling
3. LCD and control panel
4. The green light "POWER" indicates a connection of the bale to power and that the main switch is turned ON
5. Emergency "STOP" switch
6. Button "START" - starts the pressing process
7. Buttons "THROW-OFF". Two-handed operation – controler for the bale ejector

Gallery



Contact

Headquater

ARTechnic
ul. Gen. St. Maczka 9
43-300 Bielsko-Biała
Poland

Phones

Tel. +48 (33) 816 01 69
fax +48 (33) 443 20 46

E-mail and Web Site

biuro@artechnic.pl
www.artechnic.pl
www.belowniceuzywane.pl